# Xerox<sup>®</sup> AltaLink<sup>®</sup> Multifunction Printers

**Xerox**<sup>™</sup>

B8145/B8155/B8170



AltaLink® B8100 Series Multifunction Printers are built on Xerox® ConnectKey® Technology. For more information, go to www.ConnectKey.com.

System Specification	AltaLink® B8145	AltaLink® B8155	AltaLink® B8170
Speed <sup>1</sup>	Up to 45 ppm	Up to 55 ppm	Up to 72 ppm
Monthly Duty Cycle <sup>2</sup>	Up to 200,000 pages	Up to 250,000 pages	Up to 300,000 pages
Hard Drive/ Processor/Memory	Minimum 128 GB SSD/ <b>Optional:</b> 500 GB HDD/Inte	® Atom™ Quad Core 1.91 GHz/4 GB system memory	
Connectivity	Ethernet 10/100/1000 Base-T, High-speed USB 2.0	direct print, NFC; <b>Optional:</b> WiFi/WiFi Direct with Xero	ox Dual Band Wireless Kit, Bluetooth (iBeacon)
Controller Features	Unified Address Book, Remote Control Panel, Configu	ıration Cloning, Fleet Orchestrator, Configuration Wat	chdog
Copy and Print			
Copy and Print Resolution	<b>Copy:</b> Up to 600 x 600 dpi; <b>Print:</b> Up to 1200 x 240	0 dpi	
First-Print-Out Time (as fast as)	3.8 seconds	3.2 seconds	3.0 seconds
First-Copy-Out Time (as fast as) (from platen/ warmed-up state)	4.4 seconds	3.7 seconds	3.2 seconds
Page Description Language	Adobe® PostScript® 3™, Adobe® PDF, PCL® 5c/PCL® 6		
Print Features	Print from USB, Print from Cloud Repositories (Dropbox, OneDrive, and Google Drive), Encrypted Secure Print, Xerox® Earth Smart Driver Settings, Job Identification, Booklet Layout, Store and Recall Driver Settings, Bi-directional Real-time Status, Scaling, Job Monitoring, Application Defaults, Two-sided Printing (as default), Hold All Jobs, Long Sheet (Banner) Printing, Print Around, Print on Alternate Paper, Imaging Security with AltaLink's proprietary marking and infrared detection technology; Optional: Print from and Scan to Xerox® DocuShare® Go content management		
Mobile- and Cloud-Ready			
Mobile Connectivity	Near Field Communication (NFC); <b>Optional:</b> Wi-Fi D	irect, Wi-Fi (802.11 b/g/n/ac), AirPrint (iOS) including	iBeacon (Bluetooth)
Mobile Printing	Mopria® Scan, Apple AirPrint™, Xerox® Print Service (Android), @PrintByXerox App; <b>Optional:</b> Xerox® Workplace Mobile App (iOS/Android)		
Mobile Scanning	Mopria® Scan, Apple AirPrint™, <b>Optional:</b> Xerox® Wo	rkplace Mobile App (iOS/Android)	
Mobile Apps and Xerox App Gallery	Automate everyday processes with apps that translate, redact, eSign, personalize, print, convert, route, collaborate, and communicate.  Visit xerox.com/WorkplaceApps to find apps by industry or workflow. Software and services: Xerox® DocuShare® (xerox.com/ecm),  XMPie® (xerox.com/XMPie), Xerox® Workplace Solutions (xerox.com/WorkplaceSolutions).		
Xerox® Workplace Central Platform	One-platform consistency for seamless productivity across computers, mobile devices and printers. With Workflow Central's ever-expanding suite of cloud-based workflows you can change documents into audio files for easy listening, convert PDF or image files to popular Microsoft formats for shareability with a wider audience, turn handwriting into legible, editable and shareable text, translate to/from over 40 different languages, and automatically redact Personal Identifiable Information using set words or phrases.		
Xerox® Workplace Suite and Xerox® Workplace Cloud	Optional: Xerox® Workplace Suite is a modular set of workflows designed to save customers time and money by providing effective control over their printer fleet while enabling worker productivity and mobility through a set of robust workflows. Xerox enables ultimate customer flexibility by offering these capabilities in both an on-premises server version (Workplace Suite) and with a cloud-based version (Workplace Cloud) of this solution.		
Cloud Identity Provider (IdP) Integration	Use your desktop, laptop, or mobile login credential Ping Identity, and Microsoft® Azure.	s to log in to your AltaLink® MFPs with direct connecti	ons to popular cloud identity providers, Okta,

Scan	
Standard Features	Destinations: Scan to USB/Email/Network (FTP/SMB), HTTP, HTTPS, SFTP destinations; File Formats: PDF, PDF/A, JPEG, TIFF; Convenience Features: Scan Preview, Scan to Home, Searchable PDF, Touchless Workflow Accelerators, Single/Multi-Page PDF/TIFF, Password-protected PDF, Unified Address Book, Optical Character Recognition (OCR), Scan to Folder, 1-Touch Apps, TWAIN Support, Imaging Security with AltaLink's proprietary marking and infrared detection technology
Optional Features	Scan to Cloud Repositories (Dropbox, OneDrive, and Google Drive). Xerox® Scanning App for DocuShare®, other solutions available through various Xerox® Business Innovation Partners at xerox.com/Software-Solutions, Print from and Scan to Xerox® DocuShare® Go content management
Fax	
Standard Features	Internet Fax, Network Server Fax Enablement, Fax Build Job
Optional Features	Walk-up Fax (one-line and two-line options available, includes LAN Fax, Direct Fax, Fax Forward to Email or SMB Share)
Security	
Standard Features	802.1x, IPsec, HTTPS, SFTP, and Encrypted Email, McAfee® Embedded Control Whitelisting, McAfee® ePolicy Orchestrator®, McAfee Enterprise Security Manager, LogRhythm SIEM, Network Authentication, SNMPv3, SHA-256 Hash Message Authentication, TLS 1.1/1.2/1.3, Security Certificates utilizing ECDSA, Automatic Self-signed Certificate, Cisco® Identity Services Engine (ISE) integration, automated threat response through McAfee® DXL/Cisco® pxGrid integration, Local Authentication (Internal Database), FIPS 140-2. User Access and Internal Firewall, Port/IP/Domain Filtering, Audit Log. Access Control, User Permissions, Configuration Watchdog, TPM, Trusted Boot, Encrypted Storage Drive (AES 256-bit, FIPS 140-2), Firmware Verification, Job Level Encryption via HTTPS and Drivers, Signed Email, Common Criteria Certification (ISO 15408) full system against HCP PP, Encrypted Secure Print, Imaging Security (copy, print, scan, email) with AltaLink's proprietary infrared detection technology
Optional Features	McAfee® Integrity Control, Smart Card Enablement Kit (CAC/PIV/.NET)³, Xerox® Integrated RFID Card Reader, Encrypted Hard Disk (AES 256-bit, FIPS 140-2) with multi-pass Image Overwrite³, Xerox® Workplace Cloud/Suite Print Management and Content Security; learn more at xerox.com/WorkplaceSolutions
Print Management	
Standard Features	Xerox® Standard Accounting (Copy, Print, Scan, Fax, Email), Network Accounting Enablement
Optional Features	Xerox® Workplace Cloud/Suite, other network accounting solutions available through various Xerox® Business Innovation Partners. Xerox® Virtual Print Management Services; learn more at xerox.com/PrintManagement

#### Features and Accessories

#### Single-Pass Duplex Automatic Document Feeder (DADF)

saves time by simultaneously scanning both sides of a document with up to 270 impressions per minute (ipm).



#### **USER INTERFACE**



Intuitive Tablet-like 10.1-inch Color Touchscreen is customizable and lets you perform tasks in just a few taps. Try it out at xerox.com/AltaLink8100UI.

#### **INNOVATIVE TECHNOLOGIES**

#### PAPER INPUT<sup>4</sup>

Two 520-sheet Adjustable Trays (common with all configurations). Tray 1 handles media sizes up to 11.7 x 17 in./A3 and Tray 2 handles media sizes up to 12 x 18 in./SRA3.



**Envelope Kit** (optional — replaces Tray 1) provides feeding of up to 60 envelopes.



High Capacity Tandem Tray Configuration holds a total paper capacity of up to 3,140 sheets.

Bypass Tray handles up to 100 sheets; Custom sizes: 3.5 x 3.9 in. to 12.6 x 52 in./89 x 98 mm to 320 x 1,320 mm.



Feeder (optional) holds 3.000 sheets of letter/A4 paper, increasing the maximum paper capacity to 6,140 sheets.





Xerox® Integrated RFID Card Reader (optional) adds card-based authentication with support for over 90 access cards.



#### Near Field Communication (NFC)

Tap-to-Pair allows users to tap their mobile devices to the AltaLink® B8100 Series user panel and quickly connect with the MFP.



Smart Proximity Sensor detects when users are nearby. It conserves energy during inactive periods and automatically activates the device when a user approaches.

#### PAPER OUTPUT/FINISHERS<sup>4</sup>









#### Office Finisher

(optional) provides advanced finishing functions, optional crease/score, and saddle-stitch booklet, capable of 60-page booklets (2 to 15 sheets).

**Business Ready** (BR) Finisher (optional) gives you advanced finishing functions at a great value.

C-Fold/Z-Fold Unit (optional) adds C-fold, Z-fold, and Z-half-fold capability to the BR Finisher or BR Booklet Maker Finisher.

BR Booklet Maker Finisher (optional) creates 64-page saddle-stitched booklets (2 to 16 sheets).

#### LONG SHEET PRINTING

Long Sheet Feed Kit (optional) provides the ability to print up to 12.6 x 52 in./ 320 x 1.320 mm media.





**Dual Offset Catch Tray** (available when no finishers are installed; Single Offset Catch Tray with finishers).



Integrated Office Finisher (optional with B8145/B8155) provides 500-sheet stacking and 50-sheet, 2-position stapling.



Convenience Stapler (optional) staples up to 50 sheets of 20 lb./75 gsm media.

Device Specification			
Control Panel Languages	US English, International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Turkish, Greek, Russian, Czech, Polish, Hungarian, Romanian, Catalan, Arabic		
Accessories			
Optional	SOOGB HDD Bluetooth Kit Booklet Maker for Office Finisher BR (Business Ready) Finisher (requires Horizontal Transport Kit) BR Booklet Maker Finisher (requires Horizontal Transport Kit) C-fold/Z-fold Unit for BR Finisher or BR Booklet Maker Convenience Stapler (includes Work Surface <sup>5</sup> ) Finisher Foreign Device Interface (Also known as Auxiliary Access Device) Interface for third-party access control devices, such as coin machines and card readers Envelope Tray (Replaces Tray 1) High Capacity Feeder 3000 A4/Letter Hole Punch (2/3, 2/4, Swedish) Horizontal Transport Kit Integrated Office Finisher (Available with AltaLink® B8145, B8155) Long Sheet Feed Kit (banner printing) McAfee® Integrity Control Enablement Kit Multi-feed Detection Kit (AltaLink® B8170 only) Office Finisher Scan To Cloud Enablement Kit Smart Card Enablement Kit Smart Card Enablement Kit Walk-up Fax (One- or Two-line options, includes LAN Fax) Wi-Fi/Wi-Fi Direct with Dual Band Wireless Kit Unicode Font Kit USB Keyboard/Shelf Kit Xerox® Integrated RFID Card Reader Kit		
Electrical Requirements	AltaLink® B8145 AltaLink® B8155 AltaLink® B8170		
North America	Voltage: 110-127 VAC +/- 10%         Voltage: 110-127 VAC +/- 10%           Frequency: 50/60 Hz +/- 3%, 15 A         Frequency: 50/60 Hz +/- 3%, 20 A		
Europe	Voltage: 220-240 VAC +/- 10%       Voltage: 220-240 VAC +/- 10%         Frequency: 50/60 Hz +/- 3%, 10 A       Frequency: 50/60 Hz +/- 3%, 10 A		

Device Specification (continued)				
Power Consumption	AltaLink® B8145	AltaLink® B8155	AltaLink® B8170	
Running (Average)	115V: 717 watts 230V: 674 watts	115V: 806 watts 230V: 760 watts	115V: 929 watts 230V: 908 watts	
Standby Mode	115V: 71 watts 230V: 71 watts	115V: 72 watts 230V: 70.3 watts	115V: 91.1 watts 230V: 79 watts	
Auto Off/Sleep Mode	115V: 0.67 watts 230V: 0.71 watts (Default time to sleep mode = 0 minutes)	115V: 0.67 watts 230V: 0.71 watts (Default time to sleep mode = 0 minutes)	115V: 0.68 watts 230V: 0.75 watts (Default time to sleep mode = 0 minutes)	
Warm-up (from Off)	As fast as 8.5 seconds			
Recovery from Sleep	As fast as 4.5 seconds			
Operating Environment				
Required Temperature Range	50 to 82° F/10 to 28° C			
Required Relative Humidity	15% to 85%			
Sound Power Levels	Operating: 63.7/64.2 dB(A)         Operating: 65.2/67.3 dB(A)         Operating: 70.4 dB(A)           Standby: 4.0/4.0 dB(A)         Standby: 4.3/4.3 dB(A)         Standby: 4.3 dB(A)			
Dimensions and Weight				
Base Configuration	Width: 24.4 in./620 mm Depth: 28.5 in./723 mm Height: 44.5 in./1,130 mm Weight: 286 lb./129.5 kg		Width: 24.4 in./620 mm Depth: 31.2 in./793 mm Height: 46 in./1,169 mm Weight: 319.2 lb./144.8 kg	
With Office Finisher (with Booklet Mαker)	Width: 47.5 in./1,207 mm Depth: 28.5 in./723 mm Height: 44.5 in./1,130 mm Weight: 370.3 lb./168 kg		Width: 47.5 in./1207 mm Depth: 31.2 in./793 mm Height: 46 in./1,169 mm Weight: 406 lb./184.2 kg	
Base Configuration with Business Ready (BR) Finisher	Width: 55 in./1,395 mm Depth: 28.5 in./723 mm Height: 44.5 in./1,130 mm Weight: 382.3 lb./173.4 kg Weight: 415.4 lb./188.4 kg			
Base Configuration with BR Booklet Maker Finisher	Width: 59 in./1,496.3 mm Depth: 28.5 in./723 mm Height: 44.5 in./1,130 mm Weight: 419.7 lb./190.4 kg Weight: 453.3 lb./205.6 kg			
Base Configuration with BR Booklet Maker Finisher and C-fold/Z-fold Unit	Width: 64.3 in./1,632 mm Depth: 28.5 in./723 mm Height: 44.5 in./1,130 mm Weight: 530.6 lb./240.7 kg		Width: 64.3 in./1,632 mm Depth: 31.2 in./723 mm Height: 46 in./1,169 mm Weight: 564.2 lb./255.9 kg	
Base Configuration with BR Booklet Maker Finisher, C-fold/Z-fold Unit, and High Capacity Feeder	Width: 93 in./2,361 mm Depth: 28.5 in./723 mm Height: 44.5 in./1,130 mm Weight: 598.8 lb./271.6 kg		Width: 93 in./2,361 mm Depth: 31.2 in./723 mm Height: 46 in./1,169 mm Weight: 632.8 lb./287 kg	
System Certifications/Regulo	atory Compliances			
Certifications	To view the latest list of certifications, go to <b>xerox</b> .	com/OfficeCertifications		

Paper Handling	AltaLink® B8145	AltaLink® B8155	AltaLink® B8170
Single-Pass Duplex Automat	ic Document Feeder (DADF)	<u> </u>	·
Capacity <sup>4</sup>	130 sheets		250 sheets
Speed (Up to)	82 ppm black-and-white (simplex) 141 ipm black-and-white (duplex)		135 ppm black-and-white (simplex) 270 ipm black-and-white (duplex)
Paper Sizes Sensed	3.4 x 4.9 in. to 11.7 x 17 in./85 x 125 mm to 297 x 4	32 mm	
Weights	16 lb. to 32 lb. bond/60 to 128 gsm		
Bypass Tray (Standard)			
Capacity <sup>4</sup>	100 sheets		
Sizes	<b>Custom Sizes:</b> 3.5 x 3.9 in. to 12.6 x 52 in./89 x 98 i	mm to 320 x 1320 mm (SEF); <b>Optional:</b> Long Sheet F	eed Kit (Banner Printing)
Weights	16 lb. bond to 110 lb. cover/52 to 300 gsm, <b>Long sh</b>	eets/banners (>19 in./483 mm): 28lb Bond - 120lb l	Index/106 - 220 gsm
Mediα Types	Bond Card Stock Card Stock Reloaded Custom Envelopes Glossy Card Stock Reloaded Heavyweight Card Stock Reloaded Heavyweight Card Stock Reloaded Heavyweight Glossy Card Stock Reloaded Heavyweight Glossy Card Stock Reloaded Heavyweight Glossy Card Stock Reloaded Hole Punched Labels Letterhead Lightweight Card Stock Reloaded Lightweight Glossy Card Stock Lightweight Glossy Card Stock Reloaded Lightweight Glossy Card Stock Reloaded Preprinted Recycled Transparencies  Long Sheets/Banners: Card Stock Card Stock Reloaded Lightweight Card Stock Lightweight Card Stock Lightweight Card Stock Lightweight Card Stock Reloaded		
Trays 1 and 2 (Standard)			
Capacity <sup>4</sup>	520 sheets each		
Sizes	<b>Tray 1:</b> Custom Sizes: 5.5 x 7.2 in. to 11.7 x 17 in./14 <b>Tray 2:</b> Custom Sizes: 5.5 x 7.2 in. to 12 x 18 in./140		
Weights	16 lb. bond to 110 lb. cover/52 to 300 gsm		
Mediα Types	Bond Card Stock Card Stock Card Stock Reloaded Custom Envelopes Glossy Card Stock Glossy Card Stock Reloaded Heavyweight Card Stock Heavyweight Glossy Card Stock Heavyweight Glossy Card Stock Reloaded Heavyweight Glossy Card Stock Heavyweight Glossy Card Stock Reloaded Libels Letterhead Lightweight Lightweight Card Stock Lightweight Glossy Card Stock Lightweight G		

Paper Handling (continued)	AltaLink® B8145	AltaLink® B8155	AltaLink® B8170		
High Capacity Tandem Tray	High Capacity Tandem Tray (Available with all models)				
Capacity <sup>4</sup>	<b>Tray 3:</b> 867 sheets <b>Tray 4:</b> 1,133 sheets				
Sizes	8.5 x 11 in./A4, JIS B5, Executive (7.25 x 10.5 in) LEF				
Weights	16 lb. bond to 110 lb. cover/52 to 300 gsm				
Media Types	Bond Card Stock Custom Glossy Card Stock Hole Punched Labels Letterhead Lightweight Card Stock Lightweight Glossy Card Stock Plain Preprinted				
Envelope Tray (Optional - Re	places Tray 1)				
Capacity <sup>4</sup>	Up to 60 envelopes				
Sizes	#10 Commercial (9.25 x 4.125 in.)/Monarch, DL, C5 Custom Sizes: 3.9 x 5.8 in. to 6.4 x 9.5 in./98 x 148 n	nm to 162 x 241 mm			
Weights	20 lb. to 24 lb. bond/75 to 90 gsm				
High Capacity Feeder (HCF)	(Optional with all models)				
Capacity <sup>4</sup>	3,000 sheets				
Sizes	Standard Sizes: 8.5 x 11 in. or 7.25 x 10.5 in./A4 or B	5 LEF			
Weights	16 lb. bond to 110 lb. cover/52 to 300 gsm				
Total Capacity	Total Capacity				
Device Total Capacity <sup>4</sup>	High Capacity Tandem Tray Module: 3,140 sheets High Capacity Tandem Tray Module with High Capa	city Feeder: 6,140 sheets			

Finishing	AltaLink® B8145	AltaLink® B8155	AltaLink® B8170
Output Trays (Standard) (Du	ı ıal Offset Catch Trays not available with Integrat	ed Office Finisher and limited to one with Office	Finisher and BR Finishers)
Stacking Tray Capacity <sup>4</sup>	Dual Offset Catch Tray: Up to 250 sheets each Left Side Face-up Tray: Up to 100 sheets		
Integrated Office Finisher (C	Optional with AltaLink® B8145/B8155)		
Stacking Tray Capacity <sup>4</sup>	500 sheets of 20 lb. bond/80 gsm – 8.5 x 11 in./A4	or 250 sheets of 20 lb. bond/80 gsm – 11 x 17 in./A3	
Sizes	3.5 x 3.9 in. to 11.7 x 17 in./89 x 98 mm to 297 x 43	32 mm	
Weights	16 lb. bond to 110 lb. cover/52 to 300 gsm		
Stapling	Single/Dual Position Auto-Stapling: 50 sheets maximum: Letter/A4/B5 size sheets (less t 30 sheets maximum: Legal/Tabloid/A3/B4 size shee		
Office Finisher (Optional)			
Stacking Tray Capacity <sup>4</sup>	2,000 sheets unstapled or 1,000 sheets single staple	ed or 750 sheets dual stapled (8.5 x 11 in./A4)	
Stacking Tray Sizes	8.3 x 7.2 in. to 11.7 x 17 in./210 x 182 mm to 297 x	432 mm	
Weights	16 lb. bond to 110 lb. cover/52 to 300 gsm		
Multiposition Stapling	50 sheets maximum: Letter/A4/B5 size sheets (less t 30 sheets maximum: Legal/Tabloid/A3/B4 size shee		
Hole Punch (Optional)	North America: 2/3-hole punch Europe: 2/4-hole punch Optional: 4-hole "Swedish" punch		
Booklet Maker for Office Fin	isher (Score/Crease, Saddle-stitch Staple) (Option	aal)	
Top Tray Capacity <sup>4</sup>	40 booklets (2-15 sheets per booklet – 20 lb./80 gsr	n or less)	
Sizes	Letter – 8.5 x 11 in./A4 SEF Legal – 8.5 x 14 in./B4 SEF Tabloid – 11 x 17 in./A3 SEF		
Saddle-Stitch Stapling	2-15 sheets/8-60 page booklet 16 lb. bond to 67 lb. bond/60 to 256 gsm		
Score/Crease	1-15 sheets/unstapled 18 lb. bond to 28 lb. bond/60 to 105 gsm		
Business Ready (BR) Finisher	r (Optional) (Requires Horizontal Transport Kit)		
Capacity <sup>4</sup>	Offsetting Top Tray: 500 sheets Stacking Stapling Tray: 3,000 sheets unstapled or 100 sets (dual or 4-position stapling) 11 x 17 in., 8.5	5 x 14 in./A3 or 200 sets (single-position staple) 8.5 x	11 in./A4
Sizes	3.9 x 5.8 in to 12.6 x 19.2 in/100 x 148 mm x 320 x 7.25 x 10.5 in. to 12.6 x 19 in./182 x 203 mm to 320 x 7.25 x 10.5 in. to 11 x 17 in./B5 to A3 for stapling		
Weights	16 lb. bond to 110 lb. cover/52 to 300 gsm		
Stapling	Single and multiposition stapling Auto stapling (50 sheets maximum) – 24 lb./90 gsm Letter, Legal, Tabloid, A3, A4, B4, and B5 sizes suppo		
Hole Punch	North America: 2/3-hole punch Europe: 2/4-hole punch Optional: 4-hole "Swedish" punch		
BR Booklet Maker Finisher (	Optional) (Requires Horizontal Transport Kit)		
Capacity <sup>4</sup>	Offsetting Top Tray: 500 sheets of 8.5 x 11 in./A4 ur Stacking Stapling Tray: 1,500 sheets of 8.5 x 11 in./11 x 17 in./A4/A3 unsta 200 stapled sets of 8.5 x 11 in./A4 (single-position s dual or 4-position stapling) or 100 stapled sets of 1	pled or tapling or	
Sizes	3.9 x 5.8 in to 12.6 x 19.2 in/100 x 148 mm x 320 x 7.25 x 10.5 in. to 12.6 x 19 in./182 x 203 mm to 320 7.25 x 10.5 in. to 11 x 17 in./B5 to A3 for stapling		
Weights	16 lb. bond to 110 lb. cover/52 to 300 gsm		
Stapling	Single and multiposition stapling Auto stapling (50 sheets maximum) – 24 lb./90 gsm Letter, Legal, Tabloid, A3, A4, B4, and B5 sizes suppo		
Hole Punch	North America: 2/3-hole punch Europe: 2/4-hole punch Optional: 4-hole "Swedish" punch		
Booklet Maker	Saddle-stitch 2 to 16 sheets (7 sheets at 106 to 176 Bi-fold up to 5 sheets Letter, Legal, Tabloid, A3, A4 supported	gsm coated or 5 sheets at 177 to 220 gsm coated)	

Finishing (continued)	AltaLink® B8145	AltaLink® B8155	AltaLink® B8170	
C-fold/Z-fold Unit (Optional	with BR Finisher and BR Booklet Maker Finisher)	<u> </u>		
Types	C-fold, Z-fold, and Z-half-fold			
Capacity <sup>4</sup>	40 sheets			
Sizes	C-fold and Z-fold: Letter – 8.5 x 11 in./A4 SEF only Z-half-fold: Tabloid – 11 x 17 in./A3 only			
Weights	16 lb. to 24 lb. bond/64 to 90 gsm			
Output Trays	Envelope Tray: C-fold, Z-fold, and Tri-fold Stacker Tray or Top Tray: Z-half-fold			
Convenience Stapler (Optior	nal - Includes Work Surface <sup>5</sup> )			
Capacity <sup>4</sup>	50-sheet stapling 5,000 staples Requires separate power outlet			
Сору	AltaLink® B8145	AltaLink® B8155	AltaLink® B8170	
First-Copy-Out Time (from platen/warmed up)	As fast as 4.4 seconds	As fast as 3.7 seconds	As fast as 3.2 seconds	
Sides (input:output)	1-1, 1-2, 2-2, 2-1			
Quantity	1 to 9,999			
Resolution (max)	Up to 600 x 600 dpi	Up to 600 x 600 dpi		
Reduction/Enlargement	Variable zoom from 25% to 400% in 1% incremen	ts		
Concurrency	Program-ahead to allow the job to be queued while	the initial job is processed (Copy, Print, Fax, and Scan)		
Copy Features	Annotation and Bates™ stamping Authentication for Services Auto Paper Select Auto Reduction & Enlargement (To fit selected pape Auto Tray Switching Automatic 2-sided/Duplex Booklet Creation Build Job (Enables page-level programming and also Collation Covers (Front only, front and back, back only, printed Dividers (blank) Edge Erase Features Help (Intuitive text and graphic description ID Card Copy Image Quality Adjustments Image Shift (with Auto Center option) Imaging Security Invert Image (negative or mirror image) Large Job Interrupt Multi-up (up to 15 columns by 15 rows) Sample Set Save Job Settings Single Color Stapling Touchless Workflow Accelerators Transparencies	o lets you proof each section or delete the last section I inside and out: Blank or Printed)	as the job is built)	

Print	AltaLink® B8145	AltaLink® B8155	AltaLink® B8170
Resolution (up to)	1200 x 2400 dpi	·	
Print Features	LAN Fax (requires optional Fax Kit) Long Sheet/Banner Layout/Watermark N-up (up to 16 pages per sheet) Paper Selection by Attribute Sample Print From Cloud Repositories (Drop Saved Job Secure Print with Timed Deletion Special Pages (exception page prog Store and Recall Driver Settings	ition (Standard, Enhanced, High)) er, Print ID in margins on the first page only or all p e Set	
Print from USB	Allows walk-up printing from Type A Supports direct printing from a com Supported file formats: PDF, JPEG, T Color jobs can be printed as black-a	nputer via Type B USB port TFF, PS, PCL	
Operating Systems	Windows Server 2008 SP2 (32- and Windows Server 2008 R2 (64-bit) Windows Server 2012 and R2 (64-bit) Windows Server 2012 (64-bit) Windows Server 2019 (64-bit) Windows 7 (32- and 64-bit) Windows 8 (32- and 64-bit) Windows 8.1 (32- and 64-bit) Windows 10 (32- and 64-bit) Mac OS 10.13, 10.14, 10.15 Fedora® Core Ubuntu®		
Network Protocols	TCP/IP: HTTP/HTTPS, Internet Printi Microsoft Windows Networking ove Bonjour®/AirPrint™ IPv6 Most protocols not in use can be dis		00, IPv4/IPv6, WSD
Font Capability	PCL: 93 scalable fonts, line printer, c	and bitmap font (including Cyrillic font support) Pos	stScript 3: 173 Type 1 fonts, 2 Multiple Master fonts
Xerox® Globαl Print Driver®			on-Xerox and Xerox® Devices from a single driver. It provides a nd simplifying print services management. Support for Microsoft
Xerox® Pull Print Driver	driver. The Xerox® Pull Print Driver e		single driver in a Pull Print environment. Uses a single queue and single ng assets. IT administrators no longer need to manage and configure d others.
Unified Address Book for Fax	, Internet Fax, Email, and Scan to		
Features	Services supported: Fax, Internet Fa Maximum contacts: 5,000 Contacts: Supports 1 or more destir Favorites for quick access of all servi	nations	

Scan	AltaLink® B8145	AltaLink® B8155	AltaLink® B8170
Concurrency	Scan while the system is printing concurrent jobs)	g, copying, or while it is transferring scan to network	or fax jobs (priority is for return of scanned originals and printing
Input Speed (up to)	82 ppm black-and-white and col 141 ipm black-and-white and co		135 ppm black-and-white and color (simplex) 270 ipm black-and-white and color (duplex)
Resolution	72 x 72 dpi to 600 x 600 dpi		
Bit Depth	1-bit (black-and-white), 8-bit (gr	ayscale), 24-bit (color)	
Maximum Scan Area	11 x 17 in./A3		
Scan Template Management	Support 250 scan templates Create Xerox® CentreWare® IS so	can templates and share via device cloning to other	multifunction printers' confirmation sheet options
Network Protocols	SFTP, FTP, SMB, HTTP, HTTPS		
File Compression		4 MMR compression – single or multiple pages)	, JBIG Arithmetic Compression, Deflate (for black-and-white and within
Document Management Fields (Metadata)	Metadata field consists of a fie	ork Scan to File Templates: tadata fields per network scan to file templates and eld name, default value, and other configurations ser interface for variable data input	unlimited fields within the template –
Scan Features	Auto Background and Shadow S Bound Originals Compression Quality/File Size Co Edge Erase Imaging Security Mixed Size Originals Original Type (Photo and Text, Pl Reduction/Enlargement Scan Build Job Scan Preview Single Touch Scan buttons (up to Size for Size (for mixed size origin Touchless Workflow Accelerators TWAIN Support/WIA 2.0 Support	ontrol  hoto, Text, Map, Newspaper/Magazine)  o 10) nals)	
Scan to Email (Standard)			
Scan Features	Auto send to self     Email signatures (6 lines each     Email signing (requires Smart 0     Scan to Email S/MIME Encrypt     Touchless Workflow Accelerato	Card option) tion	onfigurable), email Embedded Web Server confirmation sheet options
Directory Access	Address list via LDAP (Windows A	Active Directory, Exchange, Notes, Domino), Device	Address Book
Scan To			
Standard Features	Scan to USB Scan to Network Folder (using Se Scan to Home Scan to Network (using Secure F Scan to Email Scan to PC/Server Client (SMB or Scan to Mailbox	TP/HTTP/HTTPS)	
Optional Features	Scan to Cloud Repositories (Drop	pbox, OneDrive, and Google Drive)	
Workflow Scanning (Option	al)		
Scanning Software	Autostore v7 eCopy ShareScan v5.2 eCopy ScanStation v5.2		
Scanning Apps and Xerox App Gallery	1 . 3 .	Microsoft OneDrive, Microsoft Office 365™, Box®, Xe in the Xerox App Gallery: <b>xerox.com/AppGallery</b>	erox® Workplace Mobile App (iOS/Android)

Security	AltaLink® B8145	AltaLink® B8155	AltaLink® B8170
Features	Audit Log		
	Cisco® Identity Services Engine (ISE) compatible		
	Configuration Watchdog (Monitor and remediate     802.1x	75 security settings in the following areas):	
	- 802.1x - Admin Password Reset		
	- Audit Log		
	- Automatic Software Upgrade		
	- Email Alerts		
	- FIPS 140-2		
	- Hold All Jobs		
	Immediate Job Overwrite <sup>9</sup> Installation Policies		
	- McAfee® Embedded Control		
	- PII - Login Name		
	- PostScript Passwords		
	- Remote Services Enablement		
	- Remote Start (Mopria® or AirPrint™)		
	- Remote Start (TWAIN) - Reprint Saved Jobs		
	- Scan to Mailbox (Internal storage)		
	- Scheduled Disk Overwrite <sup>9</sup>		
	- Secure Passcode Length		
	- Secure Print Device Policies		
	- SIEM		
	- SNMP - System Timeout		
	- System Timeout - USB (Print from USB)		
	- USB (Scan to USB)		
	- USB Port Management		
	- User Data Encryption		
	Expanded Authentication		
	Digitally signed PDF (when using Smart Card au     Encrypted and authentication to SMTP server for		
	- Encrypted and additionated to Sixth Server to		
	- FIPS 140-2 256 bit Hard Disk Encryption, TLS, IF		
	- Immediate Image Overwrite/Securely delete job		
	- Local Authentication (internal database)		
		device services via Kerberos (UNIX/Windows Serve	r 2008), SMB (Windows Server 2008,
	Windows server 2012), NDS, LDAP authentication - On-demand Image Overwrite (Scheduled, Manu		
	- Secure Data	iai), includes samuation of unused area of alsk	
	- Secure Print (up to 10 digit PIN or Network Auth	nentication)	
	- Smart Card authentication — 144k CAC/PIV Card	d Support (2048 bit certificate key)/.NET	
	Expanded Authorization		
	Authorization per user per service     SA access based on network credentials		
	- SA access based on network credentials - Secure Network Access		
		int Features (e.g., time restrictions) reflects in the pri	int driver
	Full System Common Criteria certified by NIAP un		
	Hide Print Job Names	· <del>·</del>	
	• Imaging Security	2. 2. LITTD . 002.4V CETD	
	• IP Filter, IPsec, IPv6, TLS v1.0, v1.2, v1.3, SNMP v1		
	McAfee® Embedded Control (whitelisting), McAfe     Port disablement including USB ports	e miegniy control (optional)	
	Security Information and Event Management (SI)	EM) support for McAfee® Enterprise Security Manac	ger, LogRhythm, and Splunk
Xerox® Integrated RFID	Integrated support for most industry security cards		
Card Reader (Optional kit)	the multifunction printer panel	providing additional security, with embedded multi	rancaon printer cara readers III
	The second processing		

Fax	AltaLink® B8145	AltaLink® B8155	AltaLink® B8170	
Network Server Fax Features				
Compatibility	ITU (CCITT) group 3; Various Xerox® Business Innovation Partner Solutions			
Maximum Scan Area	11 x 17 in./A3			
Fax Send Features	One- or Two-sided Scanning (up to 11 x 17 in./A3) Add to Send List (200 numbers maximum) Build Job, Favorites, Delay Send (specific time) Origin	nal Type (photo, text or photo and text)		
Fax Print Features	One- or Two-sided Printing, Staple, Secure Print			
Transmission Resolution	Superfine: 400 x 200 dpi (Scan at 600 x 600 dpi) Fine: 200 x 200 dpi Standard: 200 x 100 dpi			
Internet Fax Features				
Compatibility	Direct print-ready document transmission to remote Reception and automatic printout of documents ser	Internet Fax machines or email clients (SMTP) nt via email from remote Internet Fax machines or er	nail clients	
Directory Access	Utilizes the Unified Address Book			
Send/Receive	Send: Multi-page TIFF, PDF, PDF/A Receive: TIFF, MTIFF, PDF, PDF/A, PS, text, PCL, PRN	, JPEG		
Resolution	72 x 72 dpi to 600 x 600 dpi Bit Depth: 1-bit (black-and-white)			
Network Protocols	SMTP (send), POP3 (receive)			
Compliance	ITU-T T.37 compliant			
Walk-up Fax Features (Option	nal; Customer-Installable – 1 and 2 lines)			
Compatibility	ITU (CCITT) Group 3			
Speed/Modems	One or Two V.34 modems: 33,600 bps. Less than 4 s	seconds per page transmission time		
Compression/Speed	MH/G3, MR/G3, MMR/SG3, JBIG/SG3			
Resolution	Walk-up Send: Standard: 200 x 100 dpi Fine: 200 x 200 dpi Superfine: 600 x 600 dpi Receive: Accepts all sizes			
Fax Send Features	LAN Fax (fax from print driver) Auto Fax Transmission Reduction Page-by-page Job Status at the Machine Delay Start, Build Job, Favorites Automatic Memory Resend Automatic Cover Sheets PSTN Fax Batch Send (up to memory capacity) Device Address Book (up to 5,000 contacts)			
Fax Receive Features	One- or Two-sided Printing Stapled or Unstapled Receive Print Mode – Manual (size, margin, stock, he Output Tray Selection Up to 200 Password Protected Mailboxes Secure Receive Receive Timestamp Auto Answer Delay	rader)/Auto		
Fax Forward	Forward to Email or SMB Location Fax Forward on Receive Only			
Fax Reports	Activity, Dial Directory, Group Directory, Transmissio Broadcast Report	n Confirmation, Pending Fax, Options Report, On-der	nand Overwrite <sup>9</sup> Report, Mailbox Report,	
Directory Access	Utilizes the Unified Address Book Group fax available			
Auto Redial	Up to 14 attempts (per country requirements) 1 to 25-minute intervals			
Auto Resend	Up to 5 attempts			

Device Management	
Administrative Protocols	DHCP, BOOTP, SNMP, SLP® v2, HTTP, HTTPS, DHCP Autonet, TLS, NTP, DNS, SMB, SMTP/POP3, WSD, LDAP, Multicast DNS
Management Support	SNMP Version 1. SNMP Version 2c and SNMP Version 3 trap over TCP/IP and IP MIB access (IETF-MIBII RFC 1213) Host Resources MIB RFC 2790, Printer MIB RFC 3805, PWG-Imaging-System- Power MIB, Fleet Orchestrator, Configuration Watchdog
Xerox® CentreWare® Web	A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running on Windows, UNIX, or any other operating system:  • Works with any SNMP-managed printer from any manufacturer  • Remote configuration of SNMP v3  • Provides help with device discovery and installation, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management  • Requires Windows 7 and Internet Explorer 6.0 and higher  • Auto-detect Xerox® CentreWare® Web server and download configurations files for touchless remote installation
Xerox® Device Manager	Xerox® Device Manager collects and manages the data that drives fact-based decisions for your enterprise device management environment. It is a single tool to install print queues and configure, manage, monitor, and report on both networked and locally connected devices – regardless of vendor – across your enterprise. Xerox® Device Manager provides:  • Device monitoring and troubleshooting  • Remote configuration of SNMP v3  • Extensive reporting and discovery of new devices  • Usage collection, chargeback, and billing capabilities  • Auto-detect Xerox® Device Manager server and download configurations files for touchless remote installation
Xerox® Workplace Cloud	Remote management to set and audit device configuration data with Xerox® Workplace Cloud, eliminating the need for an on-site server
Fleet Orchestrator	Fleet Orchestrator feature offers the ability to create a group of devices that share information with each other via a secure peer-to-peer connection.  The following data can be shared: Software update files, clone files, and 1-Touch App files. Auto-assembly feature allows a new AltaLink® to automatically set itself on the network and configure.
Novell NDPS/NEPS	Server gateway application: centralized management tool
Xerox® Device Types for SAP R/3 Intelligent Barcode Utility (optional)	Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer in specific versions of SAP environment and within Latin-1 (ISO8859-1) SAP system code pages only. Used in conjunction with Xerox® PostScript Device Types for SAP environment and Xerox® Font Center Barcode Fonts. For more information, visit office.xerox.com/Software-Solutions
Xerox® Device Types for SAP Environment	Xerox, together with SAP through our Gold-level membership in the SAP Printer Vendor Program, provides seamless connectivity between SAP systems and your Xerox® Printers and Multifunction Printers. As an SAP customer, you benefit from having SAP-certified Xerox® Device types available right from SAP's online delivery model. SAP-certified device types for Xerox® Printers and Multifunction Printers are available to download.  office.xerox.com/Software-Solutions
Xerox® Embedded Web Server – Integrated Device Web Pages Provided by the Device	
Device Status	Web server embedded in Network Controller:  • Tray status/contents  • Consumables status  • Alerts  • Remote Control Panel
Job Submission	Print-ready files: PS, PCL, TIFF, PDF, JPG, TXT, PRN Output feature selection (2-sided, collate, orientation, staple, hole punch, folding, output destination) Delivery options (Immediate, sample set, delay and secure, Save job or reprint)
Device Administration	Allows simple, remote installation setting of configuration options and management of the device, Fleet Orchestrator
Browsers	Internet Explorer 10.x, 11.x Safari 10.x, 11.x Mozilla Firefox 45.x through 53.x Opera 25.x through 53.x Chrome 48.x through 72.x
Support	Install print/scan drivers and online support available via support.xerox.com
Languages Supported	International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Russian, Simplified Chinese, Korean, Japanese, Arabic
Remote Services	
Xerox® Automatic Meter Readings (AMR)	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® Device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.
Xerox <sup>®</sup> Automαtic Supplies Replenishment (ASR)	Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to manually manage supplies inventory.
Accounting	
Xerox® Standard Accounting (Standard)	
Tracking	Copy, Print, Fax, Scan, and Email usage
Accounting	Up to 2,497 User Accounts (User ID) Up to 500 General Accounts (Client) Up to 498 Group Accounts (Department)
Features	<ul> <li>Administrator can manage the feature via the Web User Interface or device control panel in tools.</li> <li>Administrator can import or export User Accounts, Group Accounts, General Accounts, and User Limits via an industry-standard CSV file.</li> </ul>

#### Accounting Options – Network Accounting (Allows central server to manage all accounting) • Enhanced network accounting with up-to-the-minute data on how the system is being used • Comprehensive management and enterprise-scale tracking and reporting of device usage of copy, print, scan, and server fax • Numerous solutions are available through Xerox Alliance Partners. For details, visit www.xerox.com • Security enhancements with the addition of HTTPS protocol support • Device requests account authentication from third-party server enabling larger databases of users and accounts • Accept Authentication Login at the control panel and pass to third-party Networking Account • Interface with third-party accounting terminal for accounting user interface **Supplies** Description Yield Toner Cartridge<sup>6</sup> Black 52,000 pages Transfer Belt Cleaner 1 Assembly 160,000 pages Second Bias Transfer Roll 200,000 pages 1 Assembly Staple Cartridges For BR Finisher, Integrated Office Finisher, Office Finisher, and Convenience Stapler (1 cartridge per carton) 5,000 each cartridge For BR Booklet Maker (1 cartridge per carton) 5,000 each cartridge For Office Finisher Booklet Maker (8 cartridges per carton) 2,000 each cartridge For Integrated Office Finisher, Office Finisher, BR Finisher, and Convenience Stapler (3 refills per carton) Staple Refills 5,000 each refill Xerox® Smart Kit® Drum Cartridge7 1 Cartridge 200,000 pages **Waste Toner Container** 1 Cartridge (AltaLink® B8145/8155) 121,000 pages w/o Suction Filter Waste Toner Container 1 Cartridge (AltaLink® B8170) 121,000 pages with Suction Filter9

Return spent imaging supplies through the Xerox® Green World Alliance® collection/reuse/recycling program. For more information, visit <a href="https://www.xerox.com/About-Xerox/Recycling">www.xerox.com/About-Xerox/Recycling</a>.

For more information, visit us at www.xerox.com/Office



<sup>&</sup>lt;sup>1</sup> Declared in accordance with ISO/IEC 24734.

 $<sup>^{2}</sup>$  Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis

<sup>3</sup> Not available in all geographies.

<sup>4</sup> Paper capacities are based on 20 lb./75 gsm stock; capacities will vary with different weight stocks.

<sup>&</sup>lt;sup>5</sup> Sold separately in some geographies.

<sup>&</sup>lt;sup>6</sup> Average standard pages. Declared in accordance with ISO/IEC 19752. Toner yield can vary due to many factors, including but not limited to image area coverage, image content, media size, media orientation, run mode, application types, monthly print volumes, and image quality set-points.

<sup>&</sup>lt;sup>7</sup> Average drum yield is based on a run length of 5 pages of 8.5 x 11 in./A4 LEF pages, with a split of 35% color/65% black-and-white pages.

<sup>8</sup> Waste Toner Container yield will vary depending on the image type, area coverage %, and job run length.

<sup>&</sup>lt;sup>9</sup>With optional hard drive.