Lexmark™
A Xerox Company

Lexmark CX963se

With the new CX963se colour A3 multifunction printer, you get reassuring versatility, exceptional sustainability and surprising simplicity from such sophisticated technology. Boost your productivity with vivid prints – up to 55 pages per minute*. Intuitively navigate the 25 cm colour touchscreen, and save time with single-pass two-sided scanning.

Print Technology
Colour Laser

Function
Colour Copying, Colour Printing, Colour Scanning, Trusted Platform Module (TPM), The Trusted Platform Module (TPM) is not available in some countries.

Workgroup Size
Large Workgroup

Touch Screen Display
Yes

Display
Lexmark e-Task 10.1-inch (25.6 cm) colour touch screen

Print Speed (A4, Black)
Up to 55 ppm[4]

Print Speed (A4, Colour)
Up to 55 ppm[4]

Print Speed (A4, Black) Duplex
Up to 55 spm[4]

Print Speed (A4, Colour) Duplex
Up to 55 spm[4]

Time to First Page (Black)
As fast as 7.1 seconds

Time to First Page (Colour)
As fast as 8.2 seconds

Duplex (2-sided) Printing
Integrated Duplex

Print Resolution, Black
1200 x 1200 dpi, 4800 Colour Quality

Print Resolution, Colour
1200 x 1200 dpi, 4800 Colour Quality

Copy Speed (A4, Black)
Up to 55 cpm[4]

Copy Speed (A4, Colour)
Up to 55 cpm[4]

Copy Speed (A4, Black) Duplex
Up to 55 spm[4]

Copy Speed (A4, Colour) Duplex
Up to 55 spm[4]

Time to First Copy (black)
As fast as 8.5 seconds

Time to First Copy (colour)
As fast as 9.5 seconds

Reduce / Enlarge Range
25 - 400 %

A4/Ltr Simplex Scan Speed (Mono)
Up to 120/120 sides per minute

A4/Ltr Simplex Scan Speed (Colour)
Up to 120/120 sides per minute

A4/Ltr Duplex Scan Speed (Mono)
Up to 240/240 sides per minute

A4/Ltr Duplex Scan Speed (Colour)
Up to 240/240 sides per minute

Scan Area, Maximum (mm)
297 x 432 mm

ADF Scan
DADF (single pass Duplex)

Scanner Type
Flatbed scanner with automatic document feeder

Scan Resolution, Enhanced
Up to 600 X 600 dpi

Scan Resolution, Optical
Up to 600 dpi

Scan File Formats (Send as)
JPEG, JPG, PDF, Secure PDF, TIFF, Archival PDF (A-1a, A-1b), Searchable PDF, TXT, RTF, DOCX

Scan Destinations
e-mail, FTP, USB Flash drive, USB or Network connected computer

Processor Speed
Quad Core, 1.2 GHz

Memory, Standard
4 GB

Memory, Maximum
4 GB

Hard Disk
Intelligent Storage Drive included; Magnetic Hard Disk (optional)

Apple Operating Systems Supported
Support is provided through AirPrint and AirScan only

Citrix MetaFrame
Microsoft Windows Server 2012 R2 Datacenter Edition running Citrix XenApp 7.5, 6, 7, 8, 9, 11, 12, 13, 14, 15, 16, Microsoft Windows Server 2012 Datacenter Edition running Citrix XenApp 7.5, 6, 7, 8, 9, 11, 12, 13, 14, 15, 16, Microsoft Windows Server 2012 Foundation running Citrix XenApp 6.0, 6.5, Microsoft Windows Server 2012 Essentials running Citrix XenApp 6.0, 6.5, Microsoft Windows Server 2012 Standard running Citrix XenApp 6.0, 6.5

Linux Operating Systems Supported
Ubuntu 20.04, Debian 10, SUSE Linux Enterprise Server 12 SP5, OpenSUSE 15.2, Debian 11, Ubuntu 22.04, Fedora 36, Fedora 37, SUSE Linux Enterprise Server 15 SP4, OpenSUSE 15.4, Red Hat Linux 8.7, Red Hat Linux 9.1

Microsoft Windows Operating Systems Supported
Windows 7, Windows 7 x64, Windows 8, Windows 8 x64, Windows Server 2012, Windows 8.1, Windows Server 2012 R2, Windows 10, Windows Server 2016, Windows Server 2019, Windows Server 2022, Windows 11

Novell Operating Systems Supported
Novell NetWare 6.5 Open Enterprise Server, Novell Open Enterprise Server 2 (SP3) on SuSE Linux Enterprise Server 10 SP4 (x86 and x64) 3, Novell Open Enterprise Server 11 (SP3) on SuSE Linux Enterprise Server 11 SP4 (x86 and x64), Novell Open Enterprise Server 11 (SP3) on SuSE Linux Enterprise Server 12 SP1 (x86 and x64), Novell Open Enterprise Server 15 (SP1) on SuSE Linux Enterprise Server 11 SP4 (x86 and x64)

Other Operating Systems Supported
Virtually any platform supporting TCP/IP

Included Paper Handling
550-Sheet Tray, 150-Sheet Multipurpose Feeder, 500-Sheet Output Bin

Optional Paper Handling
550-Sheet Tray, Offset Stacker, 500-Sheet Staple Offset Finisher, 2 x 550-Sheet Tray, 2000-Sheet Tandem Tray, Cabinet, 1,500-Sheet High-Capacity Tray, Paper Transport Unit, Folding Paper Transport Unit, 1,250-Sheet Staple Hole Punch Finisher, 2,250-Sheet Booklet Staple Hole Punch Finisher

Paper Input Capacity, Standard
Up to 700 pages 75 gsm bond

Paper Input Capacity, Maximum
Up to 4,750 pages 75 gsm bond

Paper Output Capacity, Standard
Up to 500 pages 75 gsm bond

Paper Output Capacity, Maximum
Up to 2,650 pages 75 gsm bond

Paper Weight Range Supported - Standard Tray (gsm)
60 - 300 gsm

Paper Weight Range Supported - Multipurpose Feeder (gsm)
60 - 300 gsm

A3
Yes

ADF
300-Sheet Automatic Document Feeder

ADF Paper Input Capacity
Up to 300 pages 75 gsm bond

ADF Paper Output Capacity
Up to 300 pages 75 gsm bond

Finishing Option
Yes

25EMEA13742

Finishing Functions
Offset stacking, Stapling, Hole punching

Number of Paper Inputs, Standard
2

Number of Paper Inputs, Maximum
6

Media Types Supported
Card Stock, Envelopes, Glossy paper, Labels, Plain Paper, Vinyl Labels, Refer to the Paper & Speciality Media Guide

Media Sizes Supported
10 Envelope, 7 3/4 Envelope, 9 Envelope, A3, A4, A5, B5 Envelope, C4 Envelope, C5 Envelope, DL Envelope, Hagaki Card, Executive, Folio, JIS-B4, JIS-B5, Ledger, Legal, Letter, Statement, Oficio, A6, SRA3, 304.8 x 483 mm

Standard Ports
USB 2.0 Specification Hi-Speed Certified (Type B), Gigabit Ethernet (10/100/1000), Front USB 2.0 Specification Hi-Speed Certified port (Type A), 802.11a/b/g/n/ac + Apple iBeacon

Optional Local Ports
Internal RS-232C serial, Internal 1284-B Bidirectional Parallel

Optional Network Ports
MarkNet N8230 Fibre Ethernet Print Server

Direct USB
Yes

Ethernet Network
Yes

Wireless
Yes

Wireless Network
WPA2™ - Personal, WPA™ and WPA2™ - Personal, 802.1x Authentication: MD5, MSCHAPv2, LEAP, PEAP, TLS, TTLS

Network Protocol Support
TCP, UDP, IPSEC w/ IPv4, IPSEC w/ IPv6, ICMP, IGMP, IPv4, IPv6

Network Printing Methods
Direct IP (Port 9100), Enhanced IP (Port 9400), FTP, IPP 1.0, 1.1, 2.0 (Internet Printing Protocol), Microsoft Web Services WSD, Pull Printing, Thin Print, LPR

Network Management Protocols
WINS, APIPA (AutoIP), DHCP, DNS, DDNS, mDNS, ARP, BOOTP

Network Security
SNMPv3, 802.1x Authentication: MD5, MSCHAPv2, LEAP, PEAP, TLS, TTLS, Certificate Management, SSL Cipher Configuration, TCP/UDP Port Access Control, Security Port Lockdown, TCP Restricted Server List, IPSEC Support (IPv4/IPv6)

Printable Area (metric)
4 mm of the top, bottom, right and left edges (within)

Printer Languages (Standard)
PCL 6 Emulation, Personal Printer Data Stream (PPDS), PostScript 3 Emulation, Direct Image, PDF 1.7 emulation, PCLm, PCL 5 Emulation

Fonts and Symbol Sets
39 scalable PPDS fonts, 5 PPDS bitmap fonts, 2 PCL 5/6 bitmap fonts, 163 scalable PostScript fonts, 94 scalable PCL 5/6 fonts

Laser Cartridge Yields (up to)[3]
, 46,900-page Colour (CMY) Cartridges, 47,700-page Black Cartridge

Imaging Unit Estimated Yield
Up to 225,000 (black) and 250,000 (colour) pages, based on 5 average letter/A4 size pages per print job and ~ 5% coverage for CS/CX96x, CX83x, CX95x, and MX95x printer series, or based on 3 average letter/A4 size pages per print job and ~ 5% coverage for all other printers

Cartridge(s) Shipping with Product
12,000-page Colour (CMY) Toner Cartridges, 15,000-page Black Toner Cartridge

Replacement Cartridges:
Product functions only with replacement cartridges designed for use in a specific geographical region. See www.lexmark.com/regions for more details.

Packaged Size (mm - H x W x D)
1080 x 740 x 785 mm

Packaged Weight, kg
110.5 kg

Size (mm - H x W x D)
858 x 592 x 660 mm

Weight
90.1 kg

Noise Level, Idle
15 dBA

Noise Level (Print), Operating
51 dBA

Duplex Print Noise Level, Operating
53 dBA

Noise Level (Copy), Operating
52 dBA

Noise Level (Scan), Operating
50 dBA

ENERGY STAR
Yes

Average Power (Hibernate Mode)
0.2 watts

Average Power (Sleep Mode)
1.2 watts

Average Power (Ready Mode)
67 watts

Average Power (Printing)
812 watts

ENERGY STAR Typical Electricity Consumption (TEC)
0.82 kilowatt-hours per week

Product Certifications
ENERGY STAR, ICES-003 Class A, BSMI Class A, VCCI Class A, FCC Class A, NOM-032, UL, cUL, NOM, US FDA/CDRH, IEC 60825-1, CB Report, ISO-532B, CE (EU) DoC, EFTA (CE), KC / KCC Mark, RCM DoC, ErP - EcoDesign, CCC, UKCA DoC, Blue Angel / DE-UZ 219, CECP, CEL, ECMA-370, TED, SII, TER, UL-AR, GS Mark, ISO-9296, EPEAT Silver, Mopria Certified®

Maximum Monthly Duty Cycle
Up to 270,000 pages per month[2]

Recommended Monthly Page Volume
7000 - 50000 Pages[1]

Specified Operating Environment
Humidity: 15 to 80% Relative Humidity, Altitude: 0 - 2,896 Metres (9,500 Feet), Temperature: 10 to 32.2°C (50 to 90°F)

Country of Origin
North America & TAA Compliant - Mexico, Rest of World - PRC

UNSPSC Code
43212110

[1]"Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage.

[2]"Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs.

[3]Average continuous black or continuous composite CMY declared cartridge yield up to this number of standard pages in accordance with ISO/IEC 19798.

[4]Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds.

Callout	Availability	Description
1	Standard	25.6 cm (10.1-inch) Colour Touch Screen
10	Optional	Paper Transport Unit
11	Optional	Folding Paper Transport Unit
12	Optional	500-Sheet Staple Finisher
13	Optional	Offset Stacker
14	Optional	1,250-Sheet Staple Hole Punch Finisher
15	Optional	2,250-Sheet Booklet Staple Hole Punch Finisher
2	Standard	500-Sheet Output Bin
3	Standard	150-Sheet Multipurpose Feeder
4	Standard	550-Sheet Tray
5	Optional	
6	Optional	2 x 550-Sheet Tray
7	Optional	2,000-Sheet Tandem Tray
8	Optional	Cabinet
9	Optional	1,500-Sheet High-Capacity Tray

25EMEA13742

© 2026 Lexmark. All rights reserved. 01/26 TSK-8351 C96SS-02EA